

-- extracted from rfc2591.txt
-- at Mon Nov 15 17:12:04 1999

DISMAN-SCHEDULE-MIB DEFINITIONS ::= BEGIN

IMPORTS

MODULE-IDENTITY,
OBJECT-TYPE,
NOTIFICATION-TYPE,
Integer32,
Unsigned32,
Counter32,
mib-2
FROM SNMPv2-SMI
TEXTUAL-CONVENTION,
DateAndTime,
RowStatus,
StorageType,
VariablePointer
FROM SNMPv2-TC
MODULE-COMPLIANCE,
OBJECT-GROUP,
NOTIFICATION-GROUP
FROM SNMPv2-CONF
SnmpAdminString
FROM SNMP-FRAMEWORK-MIB;

schedMIB MODULE-IDENTITY

LAST-UPDATED "9811171800Z" -- Nov 17, 1998 6:00:00 PM
ORGANIZATION "IETF Distributed Management Working Group"
CONTACT-INFO

"David B. Levi
Nortel Networks
4401 Great America Parkway
Santa Clara, CA 95052-8185
U.S.A.
Tel: +1 423 686 0432
E-mail: dlevi@nortelnetworks.com

Juergen Schoenwaelder
TU Braunschweig
Bueltenweg 74/75
38106 Braunschweig
Germany
Tel: +49 531 391-3283
E-mail: schoenw@ibr.cs.tu-bs.de"

DESCRIPTION

"This MIB module defines a MIB which provides mechanisms
to schedule SNMP set operations periodically or at
specific points in time."

-- 1.3.6.1.2.1.63 -- ::= { mib-2 63 }

--
-- The various groups defined within this MIB definition:
--

schedObjects OBJECT IDENTIFIER

-- 1.3.6.1.2.1.63.1 -- ::= { schedMIB 1 }

schedNotifications OBJECT IDENTIFIER

-- 1.3.6.1.2.1.63.2 -- ::= { schedMIB 2 }

schedConformance OBJECT IDENTIFIER

-- 1.3.6.1.2.1.63.3 -- ::= { schedMIB 3 }

--
-- Textual Conventions:
--

SnmpPduErrorStatus ::= TEXTUAL-CONVENTION
STATUS current

DESCRIPTION

"This TC enumerates the SNMPv1 and SNMPv2 PDU error status codes as defined in RFC 1157 and RFC 1905. It also adds a pseudo error status code `noResponse` which indicates a timeout condition."

```
SYNTAX      INTEGER {
              noResponse(-1),
              noError(0),
              tooBig(1),
              noSuchName(2),
              badValue(3),
              readOnly(4),
              genErr(5),
              noAccess(6),
              wrongType(7),
              wrongLength(8),
              wrongEncoding(9),
              wrongValue(10),
              noCreation(11),
              inconsistentValue(12),
              resourceUnavailable(13),
              commitFailed(14),
              undoFailed(15),
              authorizationError(16),
              notWritable(17),
              inconsistentName(18) }
```

```
--
-- Some scalars which provide information about the local time
-- zone.
--
```

schedLocalTime OBJECT-TYPE

```
SYNTAX      DateAndTime (SIZE (11))
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
```

"The local time used by the scheduler. Schedules which refer to calendar time will use the local time indicated by this object. An implementation *MUST* return all 11 bytes of the DateAndTime textual-convention so that a manager may retrieve the offset from GMT time."

```
-- 1.3.6.1.2.1.63.1.1 -- ::= { schedObjects 1 }
--
-- The schedule table which controls the scheduler.
--
```

schedTable OBJECT-TYPE

```
SYNTAX      SEQUENCE OF SchedEntry
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
```

"This table defines scheduled actions triggered by SNMP set operations."

```
-- 1.3.6.1.2.1.63.1.2 -- ::= { schedObjects 2 }
```

schedEntry OBJECT-TYPE

```
SYNTAX      SchedEntry
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION
```

"An entry describing a particular scheduled action."

```
INDEX {
    schedOwner,
    schedName
}
```

```
-- 1.3.6.1.2.1.63.1.2.1 -- ::= { schedTable 1 }
```

```
SchedEntry ::= SEQUENCE {
    schedOwner      SntpAdminString,
```

```

    schedName      SnmpAdminString,
    schedDescr     SnmpAdminString,
    schedInterval  Unsigned32,
    schedWeekDay   BITS,
    schedMonth     BITS,
    schedDay       BITS,
    schedHour      BITS,
    schedMinute    BITS,
    schedContextName SnmpAdminString,
    schedVariable  VariablePointer,
    schedValue     Integer32,
    schedType      INTEGER,
    schedAdminStatus INTEGER,
    schedOperStatus INTEGER,
    schedFailures  Counter32,
    schedLastFailure SnmpPduErrorStatus,
    schedLastFailed DateAndTime,
    schedStorageType StorageType,
    schedRowStatus RowStatus
}

```

schedOwner OBJECT-TYPE

```

SYNTAX      SnmpAdminString (SIZE (0..32))
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION

```

"The owner of this scheduling entry. The exact semantics of this string are subject to the security policy defined by the security administrator."

```
-- 1.3.6.1.2.1.63.1.2.1.1 -- ::= { schedEntry 1 }
```

schedName OBJECT-TYPE

```

SYNTAX      SnmpAdminString (SIZE (1..32))
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION

```

"The locally-unique, administratively assigned name for this scheduling entry. This object allows a schedOwner to have multiple entries in the schedTable."

```
-- 1.3.6.1.2.1.63.1.2.1.2 -- ::= { schedEntry 2 }
```

schedDescr OBJECT-TYPE

```

SYNTAX      SnmpAdminString
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION

```

"The human readable description of the purpose of this scheduling entry."

```
DEFVAL      { 'H' }
```

```
-- 1.3.6.1.2.1.63.1.2.1.3 -- ::= { schedEntry 3 }
```

schedInterval OBJECT-TYPE

```

SYNTAX      Unsigned32
UNITS       "seconds"
MAX-ACCESS  read-create
STATUS      current
DESCRIPTION

```

"The number of seconds between two action invocations of a periodic scheduler. Implementations must guarantee that action invocations will not occur before at least schedInterval seconds have passed."

The scheduler must ignore all periodic schedules that have a schedInterval value of 0. A periodic schedule with a scheduling interval of 0 seconds will therefore never invoke an action.

Implementations may be forced to delay invocations in the

face of local constraints. A scheduled management function should therefore not rely on the accuracy provided by the scheduler implementation."

DEFVAL { 0 }

-- 1.3.6.1.2.1.63.1.2.1.4 -- ::= { schedEntry 4 }

schedWeekDay OBJECT-TYPE

SYNTAX BITS {
 sunday(0),
 monday(1),
 tuesday(2),
 wednesday(3),
 thursday(4),
 friday(5),
 saturday(6) }

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The set of weekdays on which the scheduled action should take place. Setting multiple bits will include several weekdays in the set of possible weekdays for this schedule. Setting all bits will cause the scheduler to ignore the weekday."

DEFVAL { {} }

-- 1.3.6.1.2.1.63.1.2.1.5 -- ::= { schedEntry 5 }

schedMonth OBJECT-TYPE

SYNTAX BITS {
 january(0),
 february(1),
 march(2),
 april(3),
 may(4),
 june(5),
 july(6),
 august(7),
 september(8),
 october(9),
 november(10),
 december(11) }

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The set of months during which the scheduled action should take place. Setting multiple bits will include several months in the set of possible months for this schedule. Setting all bits will cause the scheduler to ignore the month."

DEFVAL { {} }

-- 1.3.6.1.2.1.63.1.2.1.6 -- ::= { schedEntry 6 }

schedDay OBJECT-TYPE

SYNTAX BITS {
 d1(0),
 d2(1),
 d3(2),
 d4(3),
 d5(4),
 d6(5),
 d7(6),
 d8(7),
 d9(8),
 d10(9),
 d11(10),
 d12(11),
 d13(12),
 d14(13),
 d15(14),
 d16(15),

```
d17(16),
d18(17),
d19(18),
d20(19),
d21(20),
d22(21),
d23(22),
d24(23),
d25(24),
d26(25),
d27(26),
d28(27),
d29(28),
d30(29),
d31(30),
r1(31),
r2(32),
r3(33),
r4(34),
r5(35),
r6(36),
r7(37),
r8(38),
r9(39),
r10(40),
r11(41),
r12(42),
r13(43),
r14(44),
r15(45),
r16(46),
r17(47),
r18(48),
r19(49),
r20(50),
r21(51),
r22(52),
r23(53),
r24(54),
r25(55),
r26(56),
r27(57),
r28(58),
r29(59),
r30(60),
r31(61) }
```

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The set of days in a month on which a scheduled action should take place. There are two sets of bits one can use to define the day within a month:

Enumerations starting with the letter 'd' indicate a day in a month relative to the first day of a month. The first day of the month can therefore be specified by setting the bit d1(0) and d31(30) means the last day of a month with 31 days.

Enumerations starting with the letter 'r' indicate a day in a month in reverse order, relative to the last day of a month. The last day in the month can therefore be specified by setting the bit r1(31) and r31(61) means the first day of a month with 31 days.

Setting multiple bits will include several days in the set of possible days for this schedule. Setting all bits will cause the scheduler to ignore the day within a month. Setting all bits starting with the letter 'd' or the

letter 'r' will also cause the scheduler to ignore the day within a month."

```
DEFVAL { {} }  
-- 1.3.6.1.2.1.63.1.2.1.7 -- ::= { schedEntry 7 }
```

schedHour OBJECT-TYPE

```
SYNTAX BITS {  
    h0(0),  
    h1(1),  
    h2(2),  
    h3(3),  
    h4(4),  
    h5(5),  
    h6(6),  
    h7(7),  
    h8(8),  
    h9(9),  
    h10(10),  
    h11(11),  
    h12(12),  
    h13(13),  
    h14(14),  
    h15(15),  
    h16(16),  
    h17(17),  
    h18(18),  
    h19(19),  
    h20(20),  
    h21(21),  
    h22(22),  
    h23(23) }
```

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The set of hours within a day during which the scheduled action should take place."

```
DEFVAL { {} }  
-- 1.3.6.1.2.1.63.1.2.1.8 -- ::= { schedEntry 8 }
```

schedMinute OBJECT-TYPE

```
SYNTAX BITS {  
    m0(0),  
    m1(1),  
    m2(2),  
    m3(3),  
    m4(4),  
    m5(5),  
    m6(6),  
    m7(7),  
    m8(8),  
    m9(9),  
    m10(10),  
    m11(11),  
    m12(12),  
    m13(13),  
    m14(14),  
    m15(15),  
    m16(16),  
    m17(17),  
    m18(18),  
    m19(19),  
    m20(20),  
    m21(21),  
    m22(22),  
    m23(23),  
    m24(24),  
    m25(25),  
    m26(26),  
    m27(27),
```

```

        m28(28),
        m29(29),
        m30(30),
        m31(31),
        m32(32),
        m33(33),
        m34(34),
        m35(35),
        m36(36),
        m37(37),
        m38(38),
        m39(39),
        m40(40),
        m41(41),
        m42(42),
        m43(43),
        m44(44),
        m45(45),
        m46(46),
        m47(47),
        m48(48),
        m49(49),
        m50(50),
        m51(51),
        m52(52),
        m53(53),
        m54(54),
        m55(55),
        m56(56),
        m57(57),
        m58(58),
        m59(59) }
MAX-ACCESS read-create
STATUS current
DESCRIPTION
    "The set of minutes within an hour when the scheduled action
    should take place."
DEFVAL { {} }
-- 1.3.6.1.2.1.63.1.2.1.9 -- ::= { schedEntry 9 }

```

```

schedContextName OBJECT-TYPE
    SYNTAX SnmpAdminString (SIZE (0..32))
    MAX-ACCESS read-create
    STATUS current
    DESCRIPTION
        "The context which contains the local MIB variable pointed
        to by schedVariable."
-- 1.3.6.1.2.1.63.1.2.1.10 -- ::= { schedEntry 10 }

```

```

schedVariable OBJECT-TYPE
    SYNTAX VariablePointer
    MAX-ACCESS read-create
    STATUS current
    DESCRIPTION
        "An object identifier pointing to a local MIB variable
        which resolves to an ASN.1 primitive type of INTEGER."
-- 1.3.6.1.2.1.63.1.2.1.11 -- ::= { schedEntry 11 }

```

```

schedValue OBJECT-TYPE
    SYNTAX Integer32
    MAX-ACCESS read-create
    STATUS current
    DESCRIPTION
        "The value which is written to the MIB object pointed to by
        schedVariable when the scheduler invokes an action. The
        implementation shall enforce the use of access control
        rules when performing the set operation on schedVariable.
        This is accomplished by calling the isAccessAllowed abstract
        service interface as defined in RFC 2271."

```

```
-- 1.3.6.1.2.1.63.1.2.1.12 -- ::= { schedEntry 12 }
```

schedType OBJECT-TYPE

```
SYNTAX      INTEGER {  
                periodic(1),  
                calendar(2),  
                oneshot(3) }
```

```
MAX-ACCESS  read-create
```

```
STATUS      current
```

DESCRIPTION

"The type of this schedule. The value periodic(1) indicates that this entry specifies a periodic schedule. A periodic schedule is defined by the value of schedInterval. The values of schedWeekDay, schedMonth, schedDay, schedHour and schedMinute are ignored.

The value calendar(2) indicates that this entry describes a calendar schedule. A calendar schedule is defined by the values of schedWeekDay, schedMonth, schedDay, schedHour and schedMinute. The value of schedInterval is ignored. A calendar schedule will trigger on all local times that satisfy the bits set in schedWeekDay, schedMonth, schedDay, schedHour and schedMinute.

The value oneshot(3) indicates that this entry describes a one-shot schedule. A one-shot schedule is similar to a calendar schedule with the additional feature that it disables itself by changing in the 'finished' schedOperStatus once the schedule triggers an action.

Changing a schedule's type is equivalent to deleting the old-type schedule and creating a new-type one."

```
DEFVAL      { periodic }
```

```
-- 1.3.6.1.2.1.63.1.2.1.13 -- ::= { schedEntry 13 }
```

schedAdminStatus OBJECT-TYPE

```
SYNTAX      INTEGER {  
                enabled(1),  
                disabled(2) }
```

```
MAX-ACCESS  read-create
```

```
STATUS      current
```

DESCRIPTION

"The desired state of the schedule."

```
DEFVAL      { disabled }
```

```
-- 1.3.6.1.2.1.63.1.2.1.14 -- ::= { schedEntry 14 }
```

schedOperStatus OBJECT-TYPE

```
SYNTAX      INTEGER {  
                enabled(1),  
                disabled(2),  
                finished(3) }
```

```
MAX-ACCESS  read-only
```

```
STATUS      current
```

DESCRIPTION

"The current operational state of this schedule. The state enabled(1) indicates this entry is active and that the scheduler will invoke actions at appropriate times. The disabled(2) state indicates that this entry is currently inactive and ignored by the scheduler. The finished(3) state indicates that the schedule has ended. Schedules in the finished(3) state are ignored by the scheduler. A one-shot schedule enters the finished(3) state when it deactivates itself."

```
-- 1.3.6.1.2.1.63.1.2.1.15 -- ::= { schedEntry 15 }
```

schedFailures OBJECT-TYPE

```
SYNTAX      Counter32
```

```
MAX-ACCESS  read-only
```

```
STATUS      current
```

```

    DESCRIPTION
        "This variable counts the number of failures while invoking
        the scheduled action."
-- 1.3.6.1.2.1.63.1.2.1.16 -- ::= { schedEntry 16 }

schedLastFailure OBJECT-TYPE
    SYNTAX      SnmpPduErrorStatus
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The most recent error that occurred during the invocation of
        a scheduled action. The value noError(0) is returned
        if no errors have occurred yet."
    DEFVAL      { noError }
-- 1.3.6.1.2.1.63.1.2.1.17 -- ::= { schedEntry 17 }

schedLastFailed OBJECT-TYPE
    SYNTAX      DateAndTime
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The date and time when the most recent failure occurred. The
        value '0000000000000000'H is returned if no failure occurred
        since the last re-initialization of the scheduler."
    DEFVAL      { '0000000000000000'H }
-- 1.3.6.1.2.1.63.1.2.1.18 -- ::= { schedEntry 18 }

schedStorageType OBJECT-TYPE
    SYNTAX      StorageType
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "This object defines whether this scheduled action is kept
        in volatile storage and lost upon reboot or if this row is
        backed up by non-volatile or permanent storage.
        Conceptual rows having the value `permanent' must allow
        write access to the columnar objects schedDescr,
        schedInterval, schedContextName, schedVariable, schedValue,
        and schedAdminStatus. If an implementation supports the
        schedCalendarGroup, write access must be also allowed to
        the columnar objects schedWeekDay, schedMonth, schedDay,
        schedHour, schedMinute."
    DEFVAL      { volatile }
-- 1.3.6.1.2.1.63.1.2.1.19 -- ::= { schedEntry 19 }

schedRowStatus OBJECT-TYPE
    SYNTAX      RowStatus
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The status of this scheduled action. A control that allows
        entries to be added and removed from this table.

        The minimum number of objects that need to be set during
        row creation before a row can be set to `active' are
        schedContextName, schedVariable and schedValue."
-- 1.3.6.1.2.1.63.1.2.1.20 -- ::= { schedEntry 20 }
--
-- Notifications that are emitted to indicate failures. The
-- definition of schedTraps makes notification registrations
-- reversible (see STD 58, RFC 2578).
--

schedTraps OBJECT IDENTIFIER
-- 1.3.6.1.2.1.63.2.0 -- ::= { schedNotifications 0 }

schedActionFailure NOTIFICATION-TYPE
    OBJECTS {
        schedLastFailure,

```

```

        schedLastFailed
    }
    STATUS          current
    DESCRIPTION
        "This notification is generated whenever the invocation of a
        scheduled action fails."
-- 1.3.6.1.2.1.63.2.0.1 -- ::= { schedTraps 1 }
-- conformance information

schedCompliances OBJECT IDENTIFIER
-- 1.3.6.1.2.1.63.3.1 -- ::= { schedConformance 1 }

schedGroups OBJECT IDENTIFIER
-- 1.3.6.1.2.1.63.3.2 -- ::= { schedConformance 2 }
-- compliance statements

schedCompliance MODULE-COMPLIANCE
    STATUS          current
    DESCRIPTION
        "The compliance statement for SNMP entities which implement
        the scheduling MIB."
    MODULE
    MANDATORY-GROUPS {
        schedGroup,
        schedNotificationsGroup
    }
    VARIATION        schedCalendarGroup
    DESCRIPTION
        "The schedCalendarGroup is mandatory only for those
        implementations that support calendar based schedules."
    OBJECT           schedType
    DESCRIPTION
        "The values calendar(2) or oneshot(3) are not valid for
        implementations that do not implement the
        schedCalendarGroup. Such an implementation must return
        inconsistentValue error responses for attempts to set
        schedAdminStatus to calendar(2) or oneshot(3)."
-- 1.3.6.1.2.1.63.3.1.1 -- ::= { schedCompliances 1 }

schedGroup OBJECT-GROUP
    OBJECTS {
        schedDescr,
        schedInterval,
        schedContextName,
        schedVariable,
        schedValue,
        schedType,
        schedAdminStatus,
        schedOperStatus,
        schedFailures,
        schedLastFailure,
        schedLastFailed,
        schedStorageType,
        schedRowStatus
    }
    STATUS          current
    DESCRIPTION
        "A collection of objects providing scheduling capabilities."
-- 1.3.6.1.2.1.63.3.2.1 -- ::= { schedGroups 1 }

schedCalendarGroup OBJECT-GROUP
    OBJECTS {
        schedLocalTime,
        schedWeekDay,
        schedMonth,
        schedDay,
        schedHour,
        schedMinute
    }

```

```

STATUS      current
DESCRIPTION
    "A collection of objects providing calendar based schedules."
-- 1.3.6.1.2.1.63.3.2.2 -- ::= { schedGroups 2 }

schedNotificationsGroup NOTIFICATION-GROUP
    NOTIFICATIONS {
        schedActionFailure
    }
    STATUS      current
    DESCRIPTION
        "The notifications emitted by the scheduler."
-- 1.3.6.1.2.1.63.3.2.3 -- ::= { schedGroups 3 }

```

END

```

--
-- Copyright (C) The Internet Society (1999). All Rights Reserved.
--
-- This document and translations of it may be copied and furnished to
-- others, and derivative works that comment on or otherwise explain it
-- or assist in its implementation may be prepared, copied, published
-- and distributed, in whole or in part, without restriction of any
-- kind, provided that the above copyright notice and this paragraph are
-- included on all such copies and derivative works. However, this
-- document itself may not be modified in any way, such as by removing
-- the copyright notice or references to the Internet Society or other
-- Internet organizations, except as needed for the purpose of
-- developing Internet standards in which case the procedures for
-- copyrights defined in the Internet Standards process must be
-- followed, or as required to translate it into languages other than
-- English.
--
-- The limited permissions granted above are perpetual and will not be
-- revoked by the Internet Society or its successors or assigns.
--
-- This document and the information contained herein is provided on an
-- "AS IS" basis and THE INTERNET SOCIETY AND THE INTERNET ENGINEERING
-- TASK FORCE DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING
-- BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION
-- HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF
-- MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.
--

```